


















1986 - 1987 Buick Grand National / Regal Lamps

EXTERIOR FRONT					
Low Beam Headlamps H4656	2		High Beam Headlamps H4651	2	
Parking Light2 2057A or 2057NA	2		Front Turn Signals 2057	2	
Front Sidemarkers 194	2		Under Hood Light 89	1	
EXTERIOR REAR					
Rear Tail/Turn Signals, Tail/Stop Lights 2057	2 2		Rear Sidemarkers, Tail Lights, License Plate 194	2 2 1	
Back-up Lights, High Mount Stop Light 1156	2 2		Trunk Light 1003	1	
INTERIOR					
Step/Courtesy Lights 906 (Driver) – 89 (Passenger)	1 ea		Rear Seat Courtesy Lights (T-top) 561	2	
Instrument Panel – Analog(A), Digital(D): Illumination, [A = qty 7; D = qty 5] 'Oil/Choke' Indicator*, 'Volts' Indicator*, Note: Socket has internal resistor 'Water Temp' Indicator*, 'Brake' Warning* (if E-Brake is on) , 'Fasten Belts' Indicator, Directional Signal Indicators, 'Security' Indicator, 'Service Engine Soon' Indicator*, 'Turbo Power – Economy' * (D only) 'Turbo Power – Power' * (D only) 194 * Bulb test on start	< 1 1 1 1 1 2 1 1 1 1		Instrument Panel (continued): Hi-beam Indicator, 'Cruise' Indicator 161	1 1	
			Glove Box Light, HVAC Control (manual), Console Gear Indicator 194	1 1 1	
Dome Map/Reading Light (Hard top) 211 (Dome) 1891 (Reading - option)	1 2		Rear View Mirror Map Light (option) 912	2	
SUMMARY and BULB SPECIFICATIONS					
Bulb #	Qty	Spec's			
89	2	13V, 0.58A, 7.5W, 75 lumens (initial), Single Contact Bayonet (BA15s) base, 1-7/16" length			
161	2	14V, 0.19A, 2.7W, 12.6 lumens (initial), T3-¼ Miniature Wedge (W2.1x9.5d) base, 1-1/16" (len), 13/32" (dia)			
194	varies	14V, 0.27A, 3.8W, 25 lumens (initial), T3-¼ Miniature Wedge (W2.1x9.5d) base, 1-1/16" (len), 13/32" (dia)			
211-2	1	12.8V, 0.97A, 12.4W, 150 lumens (initial), Double End Caps base, 1-23/32" length			
561	2	12.8V, 0.97A, 12.4W, 150 lumens (initial), Rigid Loop base, 1-23/32" length			
906	1	13V, 0.69A, 9W, 75 lumens (initial), T5 Miniature Wedge (W2.1x9.5d) base, 1-1/2" (len), 5/8" (dia)			
912	2	12.8V, 1A, 12.8W, 150 lumens (initial), T5 Miniature Wedge (W2.1x9.5d) base, 1-1/2" (len), 5/8" (dia)			
1003	1	12.8V, 0.94A,12W, 189 lumens (initial), Single Contact Bayonet (BA15s) base, 1-3/4" (len), ¾" (dia)			
1156	4	12.8V, 2.1A, 26.9W, 400 lumens (initial), Single Contact Bayonet (BA15s) base, 2" (len), 1" (dia)			
1891	2	14V, 0.24A, 3.4W, 25 lumens (initial), Miniature Bayonet (BA9s) base, 1-3/16" (len), 13/32" (dia)			
2057	6	12.8V, 2.1A, 26.9W, 402 lumens (initial), Double Contact Index Bayonet (BAY15d) base, 2" (len), 1" (dia)			
2057NA	2	12.8V, 2.1A, 26.9W, 300 lumens (initial), Double Contact Index Bayonet (BAY15d) base, 2" (len), 1" (dia)			
H4651	2	12.8V, 3.9A, 50W, 2 Contact Lugs, 3.94" x 6.5" (100mm x 165mm)			
H4656	2	12.8V, 2.7A, 35W, 3 Contact Lugs, 3.94" x 6.5" (100mm x 165mm)			
Note: Lamp photos are not to scale.					
Dennis L. – 11/24/2014 Rev 2					